



Motori asincroni trifase doppia polarità autofrenanti serie AD
AD series two-speed three-phase induction brake motors
Moteurs asynchrones triphasés à double polarité autofreinants série AD
Polumschaltbare asynchrone Drehstrombremsmotoren Serie AD

2/4 POLI 3000/1500 rpm - Volt 400/50 Hz - Unico avvolgimento / Single winding

TIPO TYPE	DC				AC				DC - S				POS.DC				
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	
	Nm	∞	Watt	Kg	Nm	∞	VA	Kg	Nm	∞	Watt	Kg	Nm	∞	Watt	Kg	
AD56B	2	1	5500	12	4,0	-	-	-	-	-	-	-	-	-	-	-	
	4	1	6500	12	4,0	-	-	-	-	-	-	-	-	-	-	-	
AD63C	2	4	4500	20	6,0	5	4500	40	6,0	3	4500	17	5,4	8,0	4500	11,5	4,75
	4	4	5500	20	6,0	5	5500	40	6,0	3	5500	17	5,4	8,0	5500	11,5	4,75
AD71A	2	4	7500	20	8,0	5	7500	40	8,0	4	7500	17	7,2	8,0	7500	11,5	6,25
	4	4	16000	20	8,0	5	16000	40	8,0	4	16000	17	7,2	8,0	16000	11,5	6,25
AD71B	2	4	6000	20	8,0	5	6000	40	8,0	4	6000	17	7,6	8,0	6000	11,5	6,55
	4	4	14500	20	8,0	5	14500	40	8,0	4	14500	17	7,6	8,0	14500	11,5	6,55
AD71C	2	4	5500	20	9,0	5	5500	40	9,0	4	5500	17	8,8	8,0	5500	11,5	8,00
	4	4	14000	20	9,0	5	14000	40	9,0	4	14000	17	8,8	8,0	14000	11,5	8,00
AD80A	2	8	2700	25	11,0	8	2700	70	11,0	9	2700	34	10,9	15,0	2700	16,0	9,70
	4	8	9000	25	11,0	8	9000	70	11,0	9	9000	34	10,9	15,0	9000	16,0	9,70
AD80B	2	8	2700	25	13,0	8	2700	70	13,0	9	2700	34	12,1	15,0	2700	16,0	11,00
	4	8	9000	25	13,0	8	9000	70	13,0	9	9000	34	12,1	15,0	9000	16,0	11,00
AD80C	2	8	2500	25	14,0	8	2500	70	14,0	9	2500	34	13,4	15,0	2500	16,0	12,20
	4	8	8500	25	14,0	8	8500	70	14,0	9	8500	34	13,4	15,0	8500	16,0	12,20
AD90S	2	16	2500	30	17,0	16	2500	120	17,0	10	2500	34	14,7	30,0	2500	16,0	14,30
	4	16	8500	30	17,0	16	8500	120	17,0	10	8500	34	14,7	30,0	8500	16,0	14,30
AD90L	2	16	2300	30	19,0	16	2300	120	19,0	10	2300	34	16,2	30,0	2300	16,0	15,80
	4	16	8000	30	19,0	16	8000	120	19,0	10	8000	34	16,2	30,0	8000	16,0	15,80
AD90LB	2	16	2300	30	21,0	16	2300	120	21,0	10	2300	34	18,2	30,0	2300	16,0	17,80
	4	16	7800	30	21,0	16	7800	120	21,0	10	7800	34	18,2	30,0	7800	16,0	17,80
AD100A	2	32	1600	40	27,0	45	1600	160	29,0	12	1600	40	23,8	60,0	1600	21,0	23,60
	4	32	6000	40	27,0	45	6000	160	29,0	12	6000	40	23,8	60,0	6000	21,0	23,60
AD100B	2	32	1500	40	29,5	45	1500	160	31,5	12	1500	40	26,0	60,0	1500	21,0	25,80
	4	32	5500	40	29,5	45	5500	160	31,5	12	5500	40	26,0	60,0	5500	21,0	25,80
AD112A	2	60	800	50	40,0	70	800	300	42,0	13	800	40	26,7	120,0	800	21,0	39,00
	4	60	3400	50	40,0	70	3400	300	42,0	13	3400	40	26,7	120,0	3400	21,0	39,00
AD112B	2	60	750	50	43,0	70	750	300	45,0	13	750	40	39,7	120,0	750	21,0	42,00
	4	60	3200	50	43,0	70	3200	300	45,0	13	3200	40	39,7	120,0	3200	21,0	42,00
AD132S	2	80	350	55	57,0	95	350	500	58,0	17	350	40	48,5	240,0	350	28,0	55,50
	4	80	900	55	57,0	95	900	500	58,0	17	900	40	48,5	240,0	900	28,0	55,50
AD132M	2	80	350	55	66,0	95	350	500	67,0	17	350	40	57,5	240,0	350	28,0	64,50
	4	80	850	55	66,0	95	850	500	67,0	17	850	40	57,5	240,0	850	28,0	64,50
AD132ML	2	80	350	55	66,0	95	350	500	67,0	17	350	40	57,5	240,0	350	28,0	64,50
	4	80	850	55	66,0	95	850	500	67,0	17	850	40	57,5	240,0	850	28,0	64,50
AD160M	2	150	270	85	110,0	150	270	600	105,0	23	270	45	97,0	480,0	270	38,0	110,50
	4	150	720	85	110,0	150	720	600	105,0	23	720	45	97,0	480,0	720	38,0	110,50
AD160L	2	150	225	85	121,0	150	225	600	116,0	23	225	45	108,0	480,0	225	38,0	121,50
	4	150	675	85	121,0	150	675	600	116,0	23	675	45	108,0	480,0	675	38,0	121,50
AD180M	2	260	200	100	134,0	300	200	600	134,0	-	-	-	-	480,0	200	-	135,50
	4	260	200	100	134,0	300	200	600	134,0	-	-	-	-	480,0	200	-	135,50
AD180L	2	260	200	100	149,0	300	200	600	149,0	-	-	-	-	480,0	200	-	150,50
	4	260	200	100	149,0	300	200	600	149,0	-	-	-	-	480,0	200	-	150,50
AD200L	2	400	100	100	179,0	300	100	600	179,0	-	-	-	-	480,0	100	-	180,50
	4	400	100	100	179,0	300	100	600	179,0	-	-	-	-	480,0	100	-	180,50